



RACE 4T NANO

PRODUCT DESCRIPTION:

Race 4T Nano is recommended for high-performance 4T motorcycles that delivers high power efficiency and acceleration. It exceeds the fuel economy and engine cleaning requirements. It also offers excellent engine protection and superior clutch operation in all driving conditions. Race 4T Nano is excellent in maintaining high engine power and fuel economy with longer drain interval.

APPLICATION:

Recommended for all scooters and motorcycles with 4T engines.
Suitable for Honda, Yamaha, Suzuki, Kawasaki, Korean and Chinese motorcycles.

FEATURES & BENEFITS:

- Excellent shear stability
- Provides high temperature protection
- Outstanding wet clutch protection for maximum power transfer and smooth shifting
- Excellent wear and corrosion protection
- Maximizes power and acceleration
- Added protection against harmful deposits

PERFORMANCE LEVELS: Meets and Exceeds:

- API Service Category SJ and JASO MA2

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	RACE 4T NANO					
			5W-40	10W-30	10W-40	10W-60	20W-40	20W-50
Grade			5W-40	10W-30	10W-40	10W-60	20W-40	20W-50
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	93	77	95.4	185	125	185
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	14.6	11.9	14.4	25.3	15.2	20.4
Viscosity Index (min)	ASTM D-2270	-	164	150	156	170	126	129
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm ³	0.860	0.866	0.865	0.860	0.890	0.890
Flash Point (min)	ASTM D-92	°C	230	226	228	230	236	236
Pour Point (max)	ASTM D-97	°C	-36	-36	-36	-36	-24	-24
TBN	ASTM D-2896	Mg KOH/g	7	7	7	7	7	7
CCS, (°C)	ASTM D-5293	m.Pa.S	6600 (-30)	6850 (-25)	6750 (-25)	6800 (-25)	9100 (-15)	9200 (-15)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net