



LUBREX MARINE DD40

PRODUCT DESCRIPTION:

LUBREX MARINE DD40 is formulated with highly refined, solvent de waxed and hydro treated base stocks. It contains a properly designed package of detergent and dispersing additives as well as anti-oxidizing, anticorrosion, antitrust and anti-wear attributes. Marine DD40 is a high quality, low ash, heavy duty, detergent diesel engine oil that has been specially designed to lubricate Detroit Diesel two Stroke Engines.

APPLICATION:

Marine DD40 is for naturally aspirated and turbo charged Detroit Diesel Two Stroke engines running on fuels containing not more than 0.5% sulphur. It is suitable for engines that require API CF-2/CF/CD II/CD/CC lubricants.

FEATURES & BENEFITS:

- Excellent thermal and oxidation stability and detergency.
- Extended oil life due to efficient water separating properties and BN retention.
- Excellent Anti-Rust and Anti-corrosion properties
- Excellent wear protection.
- Multipurpose Oil.
- Longer drain intervals.
- Improves engine performance, saves fuels and reduces noise.

PERFORMANCE STANDARDS: Meets and Exceeds:

- API CF-2/CF/CDII/CD/CC

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	Marine DD 40
Grade		40	40
Kinematic Viscosity @ 104°F /40°C	ASTM D-445	cSt	150
Kinematic Viscosity @ 212°F /100°C	ASTM D-445	cSt	14.5
Viscosity Index (min)	ASTM D-2270	-	95
SP. Gravity @ 60°F	ASTM D-4052	g/cm ³	0.890
Flash Point (min)	ASTM D-92	°C	230
Pour Point (max)	ASTM D-97	°C	-15
TBN	ASTM D-2896	Mg KOH/g	7

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net