



## VELOCITY GX5

### PRODUCT DESCRIPTION:

VELOCITY GX5 are semi synthetic oils for gasoline and diesel engines having high ageing resistance, effectively reduces carbon formation and high-temperature lacquer formation. Provides safe lubrication of the engine components. These oils contains low-ash additives which allow to prolong the endurance of the catalyst.

### APPLICATION:

Gasoline and light duty diesel engines found in passenger cars, Farm and construction equipment, stationary diesel engines and four stroke engines. It can be comfortably used in mixed fleet.

### FEATURES & BENEFITS:

- Superior viscosity retention
- Oxidation resistant
- Wear and friction protection
- Engine Cleanliness and low combustion residue
- Excellent detergency and dispersancy
- Protection against rubber parts
- Good TBN Retention

### PERFORMANCE LEVELS: Meets and Exceeds:

- API Service Category SG/CF

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	VELOCITY GX5			
SAE Grade			15W40	20W50	20W60	50
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	110.0	170.3	210.0	220.3
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	15.0	19.6	25.5	19.5
Viscosity Index (min)	ASTM D-2270	-	139	133	138	100
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm <sup>3</sup>	0.885	0.890	0.889	0.898
Flash Point (min)	ASTM D-92	°C	224	236	230	260
Pour Point (max)	ASTM D-97	°C	-30	-24	-24	-15
TBN	ASTM D-2896	Mg KOH/g	6.5	6.5	6.5	6.5
CCS, (°C)	ASTM D-5293	m.Pa.S	6800 (-20)	9100 (-15)	9300 (-15)	N/A

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)