

VELOCITY GX3

PRODUCT DESCRIPTION:

VELOCITY GX 3 is designed to be used for passenger cars, light trucks as well as farm equipment, especially where single type of oil is preferred. These oils contain inhibitors to combat acids formation, oxidation and foaming. This general oil is formulated with high quality mineral base stock and advance additive system.

APPLICATION:

Gasoline and light duty diesel engines found in passenger cars. Farm and construction equipment, stationary diesel engines and four stroke engines.

FEATURES & BENEFITS:

- Superior viscosity retention
- Oxidation resistant
- Wear and friction protection
- Engine Cleanliness and low combustion residue
- Excellent detergency and dispersancy

PERFORMANCE LEVELS: Meets and Exceeds:

- API Service Category SF/CD
- MIL-L-2104A

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	VELOCITY GX3				
SAE Grade			40	50	15W-40	20W-50	20W-60
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	150	212.5	110.2	172.95	243.2
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	14.5	19.5	15.0	19.5	25.7
Viscosity Index (min)	ASTM D-2270	-	95	105	145	130	136
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm ³	0.898	0.898	0.885	0.890	0.889
Flash Point (min)	ASTM D-92	°C	250	254	224	236	232
Pour Point (max)	ASTM D-97	°C	-15	-15	-30	-24	-24
TBN	ASTM D-2896	Mg KOH/g	6	6	6	6	6
CCS, (°C)	ASTM D-5293	m.Pa.S	N/A	N/A	6800 (-20)	9100 (-15)	9200 (-15)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net