



## VELOCITY CNG

### PRODUCT DESCRIPTION:

Lubrex has developed special long drain engine oils for three wheeler engines. Velocity CNG is a high performance engine oil formulated for spark ignited CNG and LNG fueled light-duty engines. It provides excellent performance in the challenging operating environment presented by CNG (Compressed natural Gas) and LNG (Liquefied Natural Gas) and offers extended interval capability.

### APPLICATION:

- 3 Wheeler Auto Rickshaw
- Light/Medium duty vehicles

### FEATURES & BENEFITS:

- Good piston and engine cleanliness
- Reduced levels of "ash" containing additives to control deposit formation
- Excellent tappet and liner wear performance in alternative fuel engines
- Delivers long drain performance protection despite higher stress of CNG combustion

### PERFORMANCE LEVELS: Meets and Exceeds:

- API Service Category SG/CD

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	VELOCITY CNG	
Grade			15W40	20W50
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	115	180
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	15.2	19.8
Viscosity Index (min)	ASTM D-2270	-	138	127
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm <sup>3</sup>	0.880	0.890
Flash Point (min)	ASTM D-92	°C	224	236
Pour Point (max)	ASTM D-97	°C	-30	-24
TBN	ASTM D-2896	Mg KOH/g	6	6
CCS, (°C)	ASTM D-5293	m.Pa.S	6800 (-20)	9200 (-15)

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)