



PERFECTA 40 LA

PRODUCT DESCRIPTION:

Perfecta 40 LA is a premium performance, heavy-duty, low ash crankcase oil specifically designed to lubricate a wide range of four-stroke natural gas and dual-fuel engines where low ash oils are recommended. It is formulated with premium quality base oils and additive technology to provide exceptional oxidation and nitration resistance, extended oil and filter life, and outstanding wear protection

APPLICATION:

- For lubrication of engines in power generation plants, with or without cogeneration, when the manufacturer requires an oil ash content up to 0.5%

FEATURES & BENEFITS:

- Outstanding oxidation and nitration resistance
- Reduced buildup of sludges
- Excellent deposit control on valves and piston
- Exceptional oxidation resistance and dispersancy
- High level of anti-wear additive

PERFORMANCE LEVELS: Meets and Exceeds:

Perfecta 40 LA meets the requirements of all major manufactureres like:

- Caterpillar
- Wärtsilä
- MAN
- MTU
- GE - Jenbacher
- MWM
- Waukesha
- Perkins

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	PERFECTA 40 LA
SAE Grade			40
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	145.95
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	15.20
Viscosity Index (min)	ASTM D-2270	-	106
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm ³	0.882
Flash Point (min)	ASTM D-92	°C	256
Pour Point (max)	ASTM D-97	°C	-15
TBN	ASTM D-2896	Mg KOH/g	5.6
Sulphatd Ash	ASTM D-871	mass %	0.5

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net