



DRIVEMAX III

PRODUCT DESCRIPTION:

Drivemax III is a fully synthetic automatic transmission fluid formulated with premium, severely hydro processed base stocks and additives that helps provide oxidation and thermal stability, friction control, load-carrying ability, corrosion and wear protection. It helps protect against the formation of deposits, sludge, varnish, foam and provide outstanding durability.

APPLICATION:

Suitable for automatic gearboxes of passenger cars, heavy duty automatic transmissions, power steering units and hydraulic systems.

FEATURES & BENEFITS:

- It provides protection against the formation of lacquers, sludge or other harmful deposits
- Exceptional stability provided by excellent base oil and extra oxidation inhibitors
- Especially effective in minimizing transmission "chatter." Helps ensure smooth, quiet action at all speeds
- It ensures fast circulation during cold weather and excellent lubrication when hot

PERFORMANCE LEVELS: Meets and Exceeds:

- GM DEXRON-III G, III H
- MB 236.3 / 236.5 / 236. 7 / 236.9 / 236.10 / 236.11 / 12
- MB 236.10 / 236.11 / 236.12
- VW G 052 025 A2, G 052 162 A1 / A2 / A6, TL 52 162
- VW G 052 990 A2, G 055 025 A2, G 055 005 A1 / A2 / A6
- HONDA ATF Z-1, ATF DW-1
- TOYOTA D-III, WS
- TOYOTA T, T-II, T-III, T-IV, JWS 3309 / 2312D / 3324, LF
- HYUNDAI/KIA SP-II, SP-III, ATF 9638
- VOLVO 97432, 1161521, 1161540, 97340
- MAZDA ATF-M III, ATF-MV
- BMW LA 2634, LT 71141, ETL 7045E
- MITSUBISHI DIAQUEEN ATF J2, J3, SP-II, SP-III, PSF 3, AYC
- ZF TE-ML 03D / 04D / 09 / 14A / 14B / 16L / 17C
- SUBARU ATF, ATF-HP
- SUZUKI JWS 3314, 3317, 2384K
- PEUGEOT Z 0001169756, 9730 AC, 9735-EJ, JWS 3309
- NISSAN 402, MATIC D/J/K/S

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	DRIVEMAX III
Grade			
Kinematic Viscosity @ 104°F / 40°C	ASTM D-7042	cSt	34.50
Kinematic Viscosity @ 212°F / 100°C	ASTM D-7042	cSt	7.25
Viscosity Index (min)	ASTM D-2270	-	180
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm ³	0.864
Flash Point (min)	ASTM D-92	°C	210
Pour Point (max)	ASTM D-97	°C	-42

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net