

DRIVEMAX CVT

PRODUCT DESCRIPTION:

Lubrex DriveMax CVT is a fully synthetic premium multi-vehicle transmission fluid for passenger cars and vans. A well-balanced fluid that provides exceptional metal-to-metal frictional properties to help prevent belt and chain slipping and help extend transmission life. It provides superior wet-clutch performance for outstanding anti-shudder durability and reduced noise, vibration and harshness. It is blended from high-performance base oils and selected additives, including friction modifiers, detergent dispersants, oxidation inhibitors, viscosity index improvers, and corrosion inhibitors.

APPLICATION:

Especially recommended for use in push belt and chain-driven continuously variable transmissions of most European, Asian, and American passenger cars and vans.

FEATURES & BENEFITS:

- Exceptional steel on steel friction durability maintains transmission performance
- Good gear wear protection prolongs the performance and life of the transmission
- High shear stability and enhanced anti foaming and air release characteristics maintain effective lubrication
- Superior wet-clutch performance for outstanding anti-shudder durability and reduced noise, vibration and harshness
- In elevated heat, guards against the harmful effects of thermal breakdown

PERFORMANCE LEVELS: Meets and Exceeds:

- Audi/VW TL 52180, G 052 180, G 052 516
- BMW 8322 0 136 376, 8322 0 429 154, EZL 799A
- Daihatsu Amix CVTF-DC, CVTF-DFE
- Dodge/Jeep NS-2, CVTF+4®, MOPAR® CVT 4
- Ford CVT23, CVT30, WSS-M2C933-A,
- GM/Saturn DEX-CVT, CVTF I-Green2
- Honda HMMF, HCF-2
- Hyundai/Kia SP-CVT 1
- Mazda CVTF 3320
- Mercedes-Benz CVT28, 236.20
- Mini Cooper EZL 799A, ZF CVT V1
- Mitsubishi DiaQueen CVTF-J1, CVTF-J4
- Nissan NS-1, NS-2, NS-3
- Punch EZL 799A
- Shell Green 1V
- Subaru e-CVTF, i-CVTF, Lineartronic® CVTF, K0425Y0710
- Suzuki CVTF 3320, TC, NS-2, CVTF Green1, CVTF Green 2
- Toyota/Lexus TC, FE

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	DRIVEMAX CVT
Grade			CVT
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	34
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	7
Viscosity Index (min)	ASTM D-2270	-	173
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm ³	0.845
Flash Point (min)	ASTM D-92	°C	220
Pour Point (max)	ASTM D-97	°C	-45
Brookfield Viscosity @ -40 °C	ASTM D-2983	°C	9000

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net