



## FARMOL UTTO MINERAL

### PRODUCT DESCRIPTION:

Farmol UTTO is an extra high performance multipurpose tractor lubricant engineered to meet or exceed transmission and hydraulic fluid requirements. It is particularly well suited for reducing wet brake and Power Take-Off (PTO) chatter. It helps protect against wear and corrosion of tractor components and has excellent anti friction properties. Farmol UTTO optimises the performance of agricultural and commercial tractors operating in a wide range of environments and conditions.

### APPLICATION:

Farmol oil is suitable for agricultural machinery in the areas of gearbox, engine, hydraulic systems and immersion brakes for heavy-duty tractors.

### FEATURES & BENEFITS:

- Guarantees easy gear changing
- High pressure-absorption capability
- Stable to oxidation
- High resistance to aging
- Universal application
- Rationalizes storage
- High wear resistance
- Good cold-start behavior

### PERFORMANCE LEVELS: Meets and Exceeds:

- API GL-4
- ALLISON C4
- Case MS 1204,6,7,9
- Caterpillar TO-2
- Ford / NewHolland FNHA-2-C-201.00
- Ford M2C-48B/C • Ford M2C-159A
- Ford M2C-86B/C • Ford M2C-134 A/B/C/D
- New Holland NH 410B
- John Deere J20 A/B/C, J14 B/C
- Massey Ferguson M1135, M1141, M1143, M 1145
- ZF TE-ML-03E, 05F, 06K

### TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	FARMOL UTTO
Grade			10W-30
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	72
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	11.6
Viscosity Index (min)	D-2270	-	152
SP. Gravity @15°C/ 60°F	D-4052	g/cm <sup>3</sup>	0.890
Flash Point (min)	D-92	°C	226
Pour Point (max)	D-97	°C	-39

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)