

## FRICTO LITHIUM GREASE MP

### PRODUCT DESCRIPTION:

Fricto Lithium MP is multipurpose grease for general lubrication under normal operating conditions and loads, formulated for lubrication of all kinds of universal applications in transport, agriculture and off road equipments operating in wet, dusty and/or dry conditions.

### APPLICATION:

Fricto Lithium MP is used for lubrication of all kinds of bearings and joints when the temperature and loading conditions are normal. Pre-eminently suitable for passenger car, light truck and leisure vehicle applications. Always avoid contamination of the grease by dust and/or dirt when applying.

### FEATURES & BENEFITS:

- Excellent mechanical stability avoiding ejection or loss of consistency during operation
- Excellent pumpability due to the low temperature characteristics and smooth texture
- Very good water resistance, even in a humid environment a sufficient lubricating film will be maintained

### MEETS OR EXCEEDS THE REQUIREMENTS OF:

- ISO 6743-9: L-XBCEA 2
- DIN 51 502: K2K -25

### TYPICAL PROPERTIES:

| TEST                                  | ASTM METHOD | FRICTO LITHIUM MP |             |
|---------------------------------------|-------------|-------------------|-------------|
|                                       |             | NLGI 2            | NLGI 3      |
| Thickener Type                        | -           | Lithium           | Lithium     |
| Color                                 | -           | Light Brown       | Light Brown |
| Texture                               | -           | Smooth            | Smooth      |
| Worked Penetration @ 25°C, 60 Strokes | D-217       | 280               | 235         |
| Dropping Point, °C                    | D-2265      | 190               | 190         |
| Base Oil Viscosity @ 40°C, cSt        | D-445       | 150               | 150         |
| Operating Temperature Range, °C       | -           | -25 to 120        | -25 to 120  |

**HEALTH & SAFETY, ENVIRONMENT:** Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)