



VELOCITY NANO RX

PRODUCT DESCRIPTION:

Velocity Nano RX is a semi synthetic lubricant fortified with proven metallo-organic anti-wear additive system which protects engines under all operating conditions by providing excellent wear control in even the most sophisticated valve train mechanisms, including those with variable valve timing. It has been expertly engineered to help deliver superior cleaning power, wear protection and outstanding performance. It helps resist degradation between oil changes, extending the time and mileage interval between oil changes.

APPLICATION:

It is recommended for all types of modern vehicles, including high-performance turbo-charged, supercharged gasoline and diesel multi-valve fuel injected engines found in passenger cars, SUVs, light vans and light trucks.

FEATURES & BENEFITS:

- Helps prevent deposits and sludge build-up to enable long engine life
- Excellent overall lubrication and wear protection performance for many driving styles
- Outstanding performance during the maximum oil change interval
- Quick cold weather starting for ultra fast protection
- Helps to extend engine life

PERFORMANCE LEVELS: Meets and Exceeds:

- API Service Category SN/CF
- ACEA A3/B3
- MB 229.3
- Renault RN0700
- Renault RN0710
- VW 502 00
- VW 505 00

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	VELOCITY NANO RX	
SAE Grade			5W-30	5W-40
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	66.95	94.85
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	11.5	15.2
Viscosity Index (min)	D-2270	-	168	170
SP. Gravity @15°C/ 60°F	D-4052	g/cm ³	0.860	0.861
Flash Point (min)	D-92	°C	228	228
Pour Point (max)	D-97	°C	-39	-39
TBN	D-2896	Mg KOH/g	7.2	7.2
CCS, (°C),	D-5800	m.Pa.S	<6600 (-30)	<6600 (-30)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net