



RACE 4T MAX

PRODUCT DESCRIPTION:

Race 4T MAX is a high quality engine oil designed for 4-stroke motorcycles. The unique synthetic blend of 4T MAX motorcycle formulation enables it to offer advantages beyond conventional motorcycle oils of similar viscosities. It offers excellent flow characteristics at low temperatures to help reduce engine wear at start-up, and provide outstanding resistance to oxidation and volatilization at high temperatures, both of which degrade the oil. Race 4T MAX protects the engine, clutch, gears and allows the best functionality of these three critical areas of the motorcycle.

APPLICATION:

Race 4T MAX is designed primarily for on-road, high-performance, 4-cycle sport bikes, however, it may be used in other types of on and off-road 4-cycle motorcycles. Race 4T MAX will help provide excellent performance in motorcycle engines that are designed with a common engine/transmission lubrication system or where the engine lubrication system is separate from the transmission system.

FEATURES & BENEFITS:

- Outstanding protection against wear of engine and transmission components
- Exceptional thermal stability
- Outstanding wet clutch protection for maximum power transfer and smooth shifting
- Maximizes power and acceleration
- Excellent shear stability
- Added protection against harmful deposits

PERFORMANCE LEVELS: Meets and Exceeds:

- API Service Category SM
- JASO MA
- JASO MA 2

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	RACE 4T MAX			
Base Stocks			Semi Synthetic			Fully Synthetic
SAE Grade			10W-30	10W-40	20W-40	10W-40
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	77	95.4	110.2	97
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	12	14.1	15.2	15.1
Viscosity Index (min)	D-2270	-	151	152	145	165
SP. Gravity @15°C	D-4052	g/cm ³	0.865	0.866	0.890	0.865
Flash Point (min)	D-92	°C	232	232	236	240
Pour Point (max)	D-97	°C	-39	-39	-36	-39
TBN	D-2896	Mg KOH/g	7.3	7.3	7.3	7.3
CCS	D-5293	m.Pa.S	6700 (-25 °C)	6800 (-25 °C)	8600 (-15 °C)	5049 (-25 °C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net