



VELOCITY SP

PRODUCT DESCRIPTION:

Velocity SP multi-grade high mileage engine oils are engineered to provide outstanding engine protection in passenger cars and light truck applications. These engine oils contain highest quality base oils and a technologically advanced additive system which includes detergents, dispersants, anti-wear and anti-friction agents as well oxidation and corrosion inhibitors. Velocity SP engine oils deliver exceptional protection and performance characteristics over the full service interval.

APPLICATION:

Recommended for passenger cars, light trucks, and other four-stroke gasoline powered equipment wherever API SP certified oils are required. These oils meet or exceed requirements for North American, Asian and European vehicles.

FEATURES & BENEFITS:

- Reduced friction for excellent protection against engine wear
- Highly resistant to viscosity and thermal breakdown from extended high temperature operation
- Fights volatility burn-off to minimize engine deposits and exhaust emissions
- Low friction formulations for improved fuel economy – certified resource conserving
- Modern additive technology protects new engines as well as older, high mileage engines

PERFORMANCE LEVELS: Meets and Exceeds:

- API SP

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	VELOCITY SP		
SAE Grade			5W-40	10W-40	20W-50
Kinematic Viscosity @ 104°F /40°C	D-445	cSt	90.0	99.05	176.95
Kinematic Viscosity @ 212°F /100°C	D-445	cSt	14.6	14.9	19.50
Viscosity Index (min)	D-2270	-	170	158	127
SP. Gravity @15°C/ 60°F	D-4052	g/cm ³	0.850	0.867	0.879
Flash Point (min)	D-92	°C	230	234	236
Pour Point (max)	D-5950	°C	-42	-39	-30
TBN	D-2896	Mg KOH/g	7.2	7.2	7.2
CCS, (°C) max	D-5800	m.Pa.S	6600 (-30)	7000 (-25)	9500 (-15)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net