



VELOCITY SP

PRODUCT DESCRIPTION:

Velocity SP 0W-16 is a fully synthetic ultra low viscosity multi-grade engine oil formulated for use in passenger cars specifying the use of oil meeting API SP, ILSAC GF-6B requirements. These oils are engineered to provide the highest levels of engine protection available. These premium engine oils contain synthetic base oils and a technologically advanced additive system which provides improved oxidation resistance, improved deposit protection, better wear protection, excellent low temperature performance and enhanced fuel economy.

APPLICATION:

Velocity SP 0W-16 is especially formulated for passenger cars specifying the use of lubricant meeting the requirements of API SP, ILSAC GF-6B.

FEATURES & BENEFITS:

- Reduced internal engine friction for improved fuel economy
- Provide extra protection against LSPI in TGD engines
- Reduced friction for excellent protection against engine wear
- Highly resistant to viscosity and thermal breakdown from extended high temperature operation
- Fights volatility burn-off to minimize engine deposits and exhaust emissions
- Modern additive technology protects new engines

PERFORMANCE LEVELS: Meets and Exceeds:

- API SP / ILSAC GF-6B

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	VELOCITY SP
SAE Grade			0W-16
Kinematic Viscosity @ 104°F /40°C	D-445	cSt	35.4
Kinematic Viscosity @ 212°F /100°C	D-445	cSt	7.2
Viscosity Index (min)	D-2270	-	172
SP. Gravity @15°C/ 60°F	D-4052	g/cm ³	0.841
Flash Point (min)	D-92	°C	228
Pour Point (max)	D-5950	°C	-45
TBN	D-2896	Mg KOH/g	7.2
CCS, (°C) max	D-5800	m.Pa.S	6200 (-35)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net