



## VELOCITY GX7

### PRODUCT DESCRIPTION:

Velocity GX7 fully synthetic engine oils are formulated with high performance base stocks and premium additive technology which helps deliver outstanding engine protection and prevent the build-up of dirt and sludge in older engines operating in all driving conditions in highways and in the city..

### APPLICATION:

Recommend for all types of modern gasoline fueled passenger cars, SUVs, vans and light trucks.

### FEATURES & BENEFITS:

- Quick cold weather starting and fast protection helps extend engine life
- Outstanding thermal and oxidation stability
- Used for all high performance gasoline engine cars equipped with direct-injection, multi-valve, and turbo-charged technologies
- Helps to improve fuel economy
- High quality detergents and dispersants keep engine parts clean.

### PERFORMANCE LEVELS: Meets and Exceeds:

- API Service Category SJ/CF

### TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	VELOCITY GX7	
SAE Grade			5W-30	5W-40
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	68.8	92.4
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	11.8	14.9
Viscosity Index (min)	D-2270	-	169	170
SP. Gravity @15°C/ 60°F	D-4052	g/cm <sup>3</sup>	0.858	0.859
Flash Point (min)	D-92	°C	230	230
Pour Point (max)	D-97	°C	-39	-39
TBN	D-2896	Mg KOH/g	8.5	7
CCS, (°C)	D-5800	m.Pa.S	6300(-30)	6200(-30)

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)