



## VELOCITY NANO FE

### PRODUCT DESCRIPTION:

Velocity Nano FE is a fully synthetic motor oil developed to meet standard PSA B71 2290 (version 2017) recommended for PSA group vehicles (Peugeot, Citroën and DS). The product offers excellent control over sludge and deposits as well as protection against engine wear. It is compatible with Euro 5 and Euro 6 diesel engines with diesel particulate filter and petrol engines with catalytic converter.

### APPLICATION:

Recommend for use in both petrol and diesel passenger cars and light commercial vehicles, in particular Peugeot and Citroën vehicles (2017 model year and older). It can also be used for Fiat, Iveco, Toyota, Honda, Mitsubishi, Subaru, Suzuki, and Mazda where OEM recommends ACEA C2-16 specifications.

### FEATURES & BENEFITS:

- Reduced fuel consumption
- Maximum oil change intervals
- Mid-SAPS emission compatible technology
- Excellent thermal and oxidation stability
- Excellent cold flow characteristics

### PERFORMANCE LEVELS:

Meets or Exceeds:

- API Service Category SN/CF
- ACEA C2
- ACEA A5/B5
- PSA B71 2290 (2017 models and older)
- Renault RN0700

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	VELOCITY NANO FE
SAE Grade			5W-30
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	Report
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	10.1
Viscosity Index (min)	D-2270	-	165
SP. Gravity @15°C/ 60°F	D-4052	g/cm <sup>3</sup>	0.844
Flash Point (min)	D-92	°C	220
Pour Point (max)	D-97	°C	-42
TBN	D-2896	Mg KOH/g	7.8
CCS, (°C)	D-5800	m.Pa.S	<6600 (-30)

All figures are based on average production values.

*The above information is supplied to the best of knowledge and belief on the basis of current industry and our own development work. Subject to amendment.*

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)