

## FARMOL STOU MINERAL

### PRODUCT DESCRIPTION:

Farmol STOU is a premium multi-functional oil especially formulated for use in agricultural equipment, engines, transmissions, and differentials with wet brake system and integrated hydraulic system. The carefully chosen base oils and additive system forms a thermal and oxidation stable oil film thus keeps the engine, gear box, differential, and hydraulic system clean and in good condition.

### APPLICATION:

Farmol oil is suitable for agricultural machinery in the areas of gearbox, engine, hydraulic systems and immersion brakes for heavy-duty tractors.

### FEATURES & BENEFITS:

- Guarantees easy gear changing
- High pressure-absorption capability
- Stable to oxidation
- High resistance to aging
- Universal application
- Rationalizes storage
- High wear resistance
- Good cold-start behavior

### PERFORMANCE LEVELS: Meets and Exceeds:

- API: CG-4 / GL-4
- ZF TE-ML 06A, B, C, R, 07B
- FORD M2C 159B, C
- FORD NH 82009201, 2, 3
- FORD M2C 86B, C, 134D
- MASSEY FERGUSON M1145, M1139, M1144
- JOHN DEERE JDM J27, J20C, J20D
- ALLISON C4 • Suitable for Wet Bakes

### TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	FARMOL STOU	
Grade			10W-30	20W-40
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	72	120
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	11.6	14.9
Viscosity Index (min)	D-2270	-	152	128
SP. Gravity @15°C/ 60°F	D-4052	g/cm <sup>3</sup>	0.890	0.890
Flash Point (min)	D-92	°C	226	236
Pour Point (max)	D-97	°C	-39	-24

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)