



VELOCITY NANO PLUS

PRODUCT DESCRIPTION:

Velocity Nano Plus are formulated from quality base stocks combined with modern performance additives to give your engine the protection and the performance you expect under a wide variety of operating conditions. It is recommended for all high performance gasoline engine cars equipped with direct-injection, multi valve & turbo-charger technologies.

APPLICATION:

Recommended for gasoline fueled automobiles and light duty trucks requiring an API SM/CF.

FEATURES & BENEFITS:

- Excellent engine cleanliness
- Engine protection under a wide variety of operating conditions
- Optimum power & performance under most severe driving conditions
- Fully compatible with all emission control devices and all gasoline grades
- Helps reduce engine wear and corrosion

PERFORMANCE LEVELS: Meets and Exceeds:

- API Service Category SN/CF
- ACEA A3/B4
- MB 229.1
- Renault RN0700/RN0710
- VW 501 01 / 505 00
- PSA B71 2300

API LICENSE:

- SAE 20W50



TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	VELOCITY NANO PLUS	
Grade			20W50	15W40
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	165.0	110
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	19.9	15.19
Viscosity Index (min)	ASTM D-2270	-	130	141
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm ³	0.890	0.885
Flash Point (min)	ASTM D-92	°C	236	226
Pour Point (max)	ASTM D-97	°C	-24	-30
TBN	ASTM D-2896	Mg KOH/g	8	8
CCS, (°C)	ASTM D-5293	m.Pa.S	9100(-15)	6600(-20)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net