



MOMENTA PLATINUM

SYNTHETIC / SEMI SYNTHETIC

PRODUCT DESCRIPTION:

Momenta Platinum is a top tier heavy duty engine oil that helps extend engine life in the most severe on and off-highway applications while delivering outstanding performance in modern high output low-emission engines fitted with EGR, DPF, DOC and SCR - Adblue NOx reduction systems. The exceptional low temperature fluidity and pumpability in combination with the sophisticated additive system ensures maximum engine wear performance and supports longer engine life. It is designed for on-road vehicles meeting Euro VI and off-road vehicles meeting EU stage IIIA, IIIB, IV and US Tier 4 emissions standards.

APPLICATION:

Momenta Platinum is developed for heavy duty vehicles requiring ACEA E6/ E7/ E9 and API CK-4 specifications. It exceeds the requirements of the heavy duty fleet such as Scania, MAN, Mercedes-Benz, Cummins, Volvo, IVECO, MTU, and Caterpillar.

SUITABLE FOR:



FEATURES & BENEFITS:

- Exceptional Soot dispersancy and wear control.
- Optimum DPF (Diesel Particulate Filter) life.
- Exceptional cold start protection.
- Excellent shear stability.
- Improved oxidation stability.
- Best-in-class engine cleanliness.

API LICENSE:

- SAE 10W-30 • 10W-40 • 15W-40



PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	0W-30	0W-40	5W-30	5W-40	10W-30	10W-40
• API	CK-4/SN	CK-4/SN	CK-4/SN	CK-4/SN	CK-4/SN	CK-4/SN
• ACEA 2016	E6/E7/E9	E6/E7/E9	E6/E7/E9	E6/E7/E9	E6/E7/E9	E6/E7/E9
• Caterpillar	ECF-3	ECF-3	ECF-3	ECF-3	ECF-3	ECF-3
• Volvo	VDS-4.5	VDS-4.5	VDS-4.5	VDS-4.5	VDS-4.5	VDS-4.5
• Cummins	CES 20086	CES 20086	CES 20086	CES 20086	CES 20086	CES 20086
• MB	-	-	228.51	228.51	228.51	228.51
• MAN	M3271-1/M3477/ M3677/M3775/ M3777	M3271-1/ M3477/M3575/ M3775	M3271-1/M3477/ M3677/M3775/ M3777	M3271-1/ M3477/M3575/ M3775	M3271-1/M3477/ M3677/M3775/ M3777	M3271-1/ M3477/M3575/ M3775
• Deutz	DQC IV-18 LA	DQC IV-18 LA	DQC IV-18 LA	DQC IV-18 LA	DQC IV-18 LA	DQC IV-18 LA
• Renault	RLD-4	RLD-4	RLD-4	RLD-4	RLD-4	RLD-4
• Scania	Low Ash	Low Ash	Low Ash	Low Ash	Low Ash	Low Ash
• Mack	EOS 4.5	EOS 4.5	EOS 4.5	EOS 4.5	EOS 4.5	EOS 4.5
• DDC	-	-	93K222	93K222	93K222	93K222
• MTU	-	-	Type 3.1	-	-	Type 3.1
• JASO	DH2	DH2	DH2	DH2	DH2	DH2



Technical Data Sheet

TYPICAL PERFORMANCE:

PARAMETERS	ASTM	UNIT	MOMENTA PLATINUM (Typical Specification)					
			0W-30	0W-40	5W-30	5W-40	10W-30	10W-40
Grade								
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	67.1	87.5	68.45	91.65	74.15	102
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	11.85	14.9	11.8	15	11.75	15.1
Viscosity Index (min)	D-2270	-	175	180	170	173	154	156
SP. Gravity @15°C/ 60°F	D-4052	g/cm ³	0.848	0.849	0.864	0.865	0.878	0.879
Flash Point (min)	D-92	°C	226	228	230	230	234	234
Pour Point (max)	D-97	°C	-42	-42	-42	-42	-39	-39
TBN	D-2896	Mg KOH/g	10	10	10	10	10	10
CCS, (°C)	D-5293	m.Pa.S	<6200 (-35°C)	<6200 (-35°C)	<6600 (-30°C)	<6600 (-30°C)	<7000 (-25°C)	<7000 (-25°C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

[™]Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.