



## VELOCITY GX9

### PRODUCT DESCRIPTION:

VELOCITY GX9 are premium quality mineral oils for gasoline and diesel engines, which can be used in all operating conditions (city traffic, road, motorways). It is suited to turbo-charged engines and is also adapted to vehicles equipped with catalytic converter and using unleaded.

### APPLICATION:

Naturally aspirated and turbocharged gasoline engines in passenger cars and light commercial vehicles. Four stroke gasoline engines and portable power equipment.

### FEATURES & BENEFITS:

- High viscosity index
- Excellent viscosity stability
- Excellent detergency and dispersancy
- Very high antiwear and anticorrosion properties
- Very good antioxidant, antirust, antifoaming properties

### PERFORMANCE LEVELS: Meets and Exceeds:

- API Service Category SL/CF
- ACEA A3/B3
- VW 505 00
- MB 229.1

### API LICENSE:

- SAE 20W-50



### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	VELOCITY GX9		
			15W40	20W50	20W60
Grade			15W40	20W50	20W60
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	110.0	172.95	236.6
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	15.12	19.5	25.2
Viscosity Index (min)	ASTM D-2270	-	140	130	136
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm <sup>3</sup>	0.885	0.890	0.889
Flash Point (min)	ASTM D-92	°C	224	234	230
Pour Point (max)	ASTM D-97	°C	-30	-24	-24
TBN	ASTM D-2896	Mg KOH/g	8	8	8
CCS, (°C)	ASTM D-5293	m.Pa.S	6700 (-20)	9200 (-15)	9300 (-15)

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)