



## VELOCITY GX9 FULLY SYNTHETIC

### PRODUCT DESCRIPTION:

Velocity GX9 fully synthetic motor oil is formulated using the unique additives technology that actively helps keep engines clean. It allows the product to provide higher levels of cleansing and protection. This oil is particularly suitable for turbo-compressed, multi-valve and direct injection engines. It meets the most difficult conditions of use (motorway, heavy urban traffic, etc.) during all seasons.

### APPLICATION:

Naturally aspirated and turbocharged gasoline engines in passenger cars and light commercial vehicles. Four stroke gasoline engines and portable power equipment.

SUITABLE FOR: 

### FEATURES & BENEFITS:

- Superior wear and corrosion protection
- Protects against start-up wear in cold conditions through excellent low-temperature fluidity
- Maintains power and economy by minimizing wear
- Superior viscosity retention
- Oxidation resistant
- Engine Cleanliness and low combustion residue

### API LICENSE:

- SAE 5W-30
- SAE 5W-40



### PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	0W-30	0W-40	5W-30	5W-40
API	SL/CF	SL/CF	SL/CF	SL/CF
ACEA-16	A5/B5	A3/B4	A5/B5	A3/B4
MB	-	229.3, 226.5	-	229.3, 226.5
JASO	MA2	MA2	MA2	MA2
RENAULT	RN0700	RN 0700/0710	RN0700	RN 0700/0710
VW	-	502 00/ 505 00	-	502 00/ 505 00



## Technical Data Sheet

**TYPICAL PERFORMANCE:**

PARAMETERS	ASTM	UNIT	VELOCITY GX9 (Typical Specification)			
			0W-30	0W-40	5W-30	5W-40
SAE Grades						
Kinematic Viscosity @ 104°F /40°C	D445	cSt	55.6	86.5	56.3	91.6
Kinematic Viscosity @ 212°F /100°C	D445	cSt	10.2	14.9	10.1	15
Viscosity Index (min)	D2270	-	175	182	170	173
SP. Gravity @15°C/ 60°F	D4052	g/cm <sup>3</sup>	0.843	0.842	0.850	0.855
Flash Point (min)	D92	°C	224	226	226	228
Pour Point (max)	D97	°C	-42	-42	-42	-42
TBN	D2896	Mg KOH/g	10	10	10	10
CCS, (°C)	D5293	m.Pa.S	<6200 (-35°C)	<6200 (-35°C)	<6600 (-30°C)	<6600 (-30°C)

**HEALTH & SAFETY, ENVIRONMENT:**

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose of an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

**HEALTH & SAFETY:**

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

**PROTECT THE ENVIRONMENT**

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

**STORAGE:**

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

<sup>™</sup>Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.