



DRIVE A MINERAL

PRODUCT DESCRIPTION:

Drive A is a multi-purpose transmission fluid, designed for use in automatic gearboxes, where GM Type A Suffix A is quoted. Its special formula enables very smooth operation of torque converters and fluid couplings of automatic transmissions.

APPLICATION:

Drive A is suitable for use in automatic transmissions of passenger cars and light-duty trucks as well as in other power shift transmissions, industrial torque converters, power steering systems and manual transmissions, where a low-viscosity fluid of GM ATF TYPE A quality is specified.

FEATURES & BENEFITS:

- Excellent oxidation stability
- High viscosity index
- Corrosion prevention
- Smoothens transmission process
- Foaming resistance
- Controlled friction properties

PERFORMANCE LEVELS: Meets or Exceeds:

- GM Type A Suffix A

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	DRIVE A
Grade			Type A
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	52
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	7.5
Viscosity Index	ASTM D2270	-	106
SP. Gravity @15°C/ 60°F	ASTM D4052	g/cm ³	TBR
Flash Point (min)	ASTM D92	°C	220
Pour Point (max)	ASTM D97	°C	-27

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.