



## LHM PLUS FLUID

### MINERAL

#### PRODUCT DESCRIPTION:

LHM Plus Fluid is high performance multipurpose mineral based brake and clutch fluid & hydraulic system fluid specially designed for use in Citroën XM, XANTIA, BX, CX, SM, GS, hydraulic power units in Citroën ID and DS sold after September 1966 (components painted green), brake circuits and hydraulic clutch control systems in utility vehicles Citroën N, P and C35, and Peugeot 405X4 vehicle level adjuster. This product is designed to protect against pump wear and provides good rates of flow throughout the system even in the most extreme temperatures & pressures.

#### APPLICATION:

- Hydraulic system of CITROEN XM, Xantia, BX, CX, SM, GS
- Hydraulic System of CITROEN ID and DS vehicles manufactured since September 1966 (parts painted in green)
- Hydraulic system on CITROEN vans N, P and C35
- Brake circuits on Ami 8, Ami Super, Dyane and Mehari since September 1977 and on 2 CV since July 1982
- Level adjuster of Peugeot 450 X4
- Hydraulic system in later Rolls-Royce and Bentley cars
- Not miscible and not compatible with synthetic fluids including synthetic fluids DOT3, DOT4, DOT5 and former CITROEN fluids of LHS 2 type

#### FEATURES & BENEFITS:

- Excellent thermal and oxidation stability
- High resistance against rust and corrosion
- Extreme fluidity at low temperature
- Exceptional high and stable VI
- Very low pour point
- Non hygroscopic

#### PERFORMANCE LEVELS: Meets or Exceeds:

- PSA PEUGEOT CITROEN B71 2710
- ISO 7308
- FORD: ESN M6C 59A

#### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	LHM PLUS FLUID
Grade			Flourescent Green
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	6.80
Viscosity Index	ASTM D2270	-	140
Density at 15 °C	ASTM D4052	kg/m <sup>3</sup>	TBR
Flash Point COC	ASTM D92	°C	200
Pour Point (max)	ASTM D97	°C	-42
Dynamic Viscosity	ASTM D5293	°C	1200 mm <sup>2</sup> /S

#### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

#### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

#### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

#### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

<sup>™</sup>Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.