



PERFECTA LA MINERAL

PRODUCT DESCRIPTION:

Perfecta LA is a premium performance, heavy-duty, low ash crankcase oil specifically designed to lubricate a wide range of four-stroke natural gas and dual-fuel engines where low-ash oils are recommended. It is formulated with premium quality base oils and additive technology to provide exceptional oxidation and nitration resistance, extended oil and filter life, and outstanding wear protection.

APPLICATION:

- Gas-fueled (natural gas and LPG) spark ignition engines where conventional passenger car motor oils are recommended
- Naturally aspirated and turbo-charged gasoline engines in passenger cars where API SM or lower performance oils are specified
- Light truck gasoline engines where API SM or lower performance oils are specified
- Four-stroke gasoline engines in portable power equipment where the manufacturer recommends conventional passenger car motor oils of API SM or lower performance

FEATURES & BENEFITS:

- Special detergent and ashless dispersant additive system preserve power and performance by providing good control of piston and ring deposits, even under high temperature conditions
- Good nitration resistance protects against CNG related valve deposits
- Very good thermal and oxidation stability
- Single oil for fleet owners with CNG, dual-fuel and gasoline vehicles

PERFORMANCE LEVELS: Meets or Exceeds:

- | | | |
|------------------|---------------|------------------------------------|
| • Caterpillar | • MWM (DEUTZ) | • Superior STGV |
| • Wartsilä | • Waukesha | • Jenbacher |
| • MAN | • Perkins | • Cummins |
| • MTU | • MDE | • Hyundai |
| • GE - Jenbacher | • MTU | • API CF (Diesel Fuel Application) |

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	PERFECTA LA	
			30	40
SAE Grade				
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D7042	cSt	11.50	14
Viscosity Index	ASTM D2270	-	95	95
SP. Gravity @15°C/ 60°F	ASTM D4052	g/cm ³	TBR	TBR
Flash Point (min)	ASTM D92	°C	220	220
Pour Point (max)	ASTM D97	°C	-9	-9
TBN	ASTM D2896	Mg KOH/g	5.6	5.6
Sulphatd Ash	ASTM D871	Wt.%	0.5	0.5

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.