



## VELOCITY NANO FULLY SYNTHETIC

### PRODUCT DESCRIPTION:

Velocity Nano is a high-quality synthetic lubricant that incorporates anti-wear protection, as well as protection against sludge and deposit formation. This multi-grade oil meets the API quality requirement (SM) for gasoline engine passenger cars, sport utility vehicles, vans and light trucks. It is designed to provide improved oxidation resistance, improved deposit protection, better wear protection and better low-temperature performance over the life of the oil.

### APPLICATION:

Recommended for gasoline fueled automobiles and light duty trucks requiring an API SM/CF.

### FEATURES & BENEFITS:

- Designed to flow at low temperatures to get to vital engine parts quickly.
- Resists oxidation thickening to maintain proper flow under severe operating conditions.
- Provides excellent deposit and wear protection.
- Improved fuel economy.
- Excellent oxidation resistance.
- Optimal engine operating temperature, owing to thermal control formula.
- Provides safe operation of catalytic exhaust converters.
- Resistant to extreme thermal load.

### PERFORMANCE LEVELS: Meets and Exceeds:

- API SM/CF
- ACEA A3/B3
- ACEA A1/B1 (0W-20, 5W-20)
- VW 501.01 / 505.00
- RN 700, RN 710
- MB 229.3

### API LICENSE:

- SAE 5W-20
- SAE 5W-30
- SAE 5W-40



### OEM Approvals:

- MB- Approval 229.3

### TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	VELOCITY NANO (FULLY SYNTHETIC)					
			0W-20	5W-20	0W-30	5W-30	5W-40	
Grade								
Kinematic Viscosity @ 104°F /40°C	D-7042	cSt	44.7	47.3	64	66.95	89.9	
Kinematic Viscosity @ 212°F /100°C	D-7042	cSt	8.5	8.90	11.5	11.5	14.9	
Viscosity Index	D-2270	-	171	162	177	168	175	
SP. Gravity @15°C/ 60°F	D-4052	g/cm <sup>3</sup>	0.845	0.850	0.843	0.851	0.851	
Flash Point (min)	D-92	°C	230	232	230	234	234	
Pour Point (max)	D-97	°C	-42	-42	-42	-42	-42	
TBN	D-2896	Mg KOH/g	8	8	8	8	8	
CCS, (°C)	D-5293	m.Pa.S	<6200 (-35°C)	<6600 (-30°C)	<6200 (-35°C)	<6600 (-30°C)	<6600 (-30°C)	

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.