



RACE 4T SYNTH HD 20W-50 SYNTHETIC

PRODUCT DESCRIPTION:

Race 4T Synth HD 20W-50 is a fully synthetic motorcycle oil tailored for use in air and water-cooled four-stroke motorbike engines and especially suitable for Harley Davidsons. Selected base oils and high-quality additive components ensure optimum lubrication, outstanding engine cleanliness and excellent friction in all operating conditions. It is exceptionally well-suited for use with or without a wet clutch.

APPLICATION:

Race 4T Synth is intended for use in four-stroke engines of scooters, mopeds, motorcycles and ATVs, which require API SN performance level, and also for motorbikes' transmissions and clutches, which need lubrication by motor oils.

FEATURES & BENEFITS:

- Stable to ageing and stable viscosity
- Excellent wear resistance
- Outstanding corrosion protection
- High engine cleanliness
- Outstanding high temperature stability

PERFORMANCE LEVELS: Meets or Exceeds:

- API SN
- JASO MA2

TYPICAL PROPERTIES:

| PARAMETERS | TEST METHOD | UNIT | RACE 4T SYNTH HD 20W-50 |
|------------------------------------|-------------|---------|-------------------------|
| Grade | | | 20W-50 |
| Kinematic Viscosity @ 104°F /40°C | D7042 | cSt | TBR |
| Kinematic Viscosity @ 212°F /100°C | D7042 | cSt | 19.5 |
| Viscosity Index | D2270 | - | 120 |
| TBN | D8698 | mgKOH/g | 7 |
| SP. Gravity @15°C/ 60°F | D4052 | g/cm3 | TBR |
| Flash Point (min) | D92 | °C | 220 |
| Pour Point (max) | D97 | °C | -24 |

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.