



DIESEL FUEL COLD FLOW IMPROVER

A combination of additives to improve fuel quality and fuel performance in diesel engines. Diesel Cold Flow Improver improves fuel pump ability in cold weather conditions without altering other diesel fuel properties. Cold weather wreaks havoc on diesel vehicles. The paraffin wax found in certain types of diesel fuel crystallizes as the temperature decreases. Wax crystals can block fuel lines and fuel filters creating drivability problems in cold weather. Diesel Cold Flow Improver modifies the wax crystal structure of diesel fuel, reducing crystal size and allowing the fuel to flow more readily in cold weather.

APPLICATION:

- Recommended for use in all diesel fuel systems
- Recommended for Tier 4 Diesel Engines

FEATURES & BENEFITS:

- Lowers cold filter plugging point of Octane Booster diesel fuel
- Anti-Gel
- Inhibits growth of wax crystals
- Improves pour point
- Reduces the need to use kerosene dilutions for flow control
- Anti-Gel protection to minus 15 Degrees F
- No environmentally harmful dyes

DIRECTIONS:

Pour entire contents of this bottle into fuel tank. One bottle treats up to 15 gallons (56.78 Liters) of diesel fuel.

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.