



DRIVE 6HP

AUTOMATIC TRANSMISSION FLUID

PRODUCT DESCRIPTION:

Drive 6HP is an Automatic Transmission Fluid (ATF) suitable for a large variety of applications. It is formulated from selected synthetic base oils and special additives which guarantees a perfect function of the automatic transmission and offers safe operation even under high stress.

APPLICATION:

Drive 6HP fluid is developed for use in the 6HP-series transmission of ZF 6HP19, 6HP21, 6HP26, 6HP28, 6HP32, 6HP34 and also for 5 speed automatic transmission 5HP-series. It is backwardly compatible with all earlier versions of ZF 4 and 5 gear passenger cars' automatic transmission.

FEATURES & BENEFITS:

- Excellent lubricating ability even at very low temperatures.
- Very good oxidation stability
- Protection against wear, corrosion and foam formation
- Neutral towards sealing materials
- Optimum power transmission ability

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- BMW ATF M 1375.4 (8322 0142516)
- Bentley Oil PY1 12995PA
- FORD MERCON SP/LV
- Hyundai SP-IV
- Jaguar Fluid 8432
- Land Rover TYK 500050
- Maserati Oil 231603
- Nissan Matic S
- Toyota Type WS
- VW / Audi G 055 005 A1/A2/A6
- ZF Lifeguardfluid6 (S671 090 255)
- FORD WSS- M2C 8432
- BMW ATF2
- JAGUAR C2C 8432
- ZF S671 090 252/253

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	DRIVE 6HP
KV @ 104°F / 40°C	D7042	cSt	TBR
KV @ 212°F / 100°C	D7042	cSt	6.1
Viscosity Index	D2270	-	140
SP. Gravity @ 15°C	D4052	g/cm3	TBR
Flash Point (min)	D92	°C	200
Pour Point (max)	D97	°C	-42

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.