



DRIVE 8HP
AUTOMATIC TRANSMISSION FLUID

PRODUCT DESCRIPTION:

Drive 8HP is an Automatic Transmission Fluid (ATF) suitable for a large variety of applications. It is formulated from selected synthetic base oils and special additives which guarantees a perfect function of the automatic transmission and offers safe operation even under high stress.

APPLICATION:

Drive 8HP is suitable for use in automatic ZF transmission of 8HP-Series 8HP45, 8HP55, 6HP26, 8HP70, 8HP90, also for ZF transmission 6-stroke automatic 6HP-series - 6HP19X for AUDI Q7, 6HP19A, 6HP28AF. It can also be used in ZF transmission series 9HP48.

FEATURES & BENEFITS:

- Reduced vibration.
- Improved lubricating
- Reduced wear and softer shifting operations due to consistent friction behavior.
- Increased sound dampening due to low viscosity.
- maximum reduction of fuel consumption, which reduces emission

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- ZF Lifeguard 8
- Audi / VW Oil No. G 060162 A1 / A2 / A6
- Jaguar Oil No. 02JDE 26444
- Land Rover Oil No. LR023288
- Chrysler Oil No. 68157995AA
- Petronas Tutela Transmission AS8
- BMW 83 222 152 426
- BMW 83 222 305 397 (ATF3)
- BMW 83 222 289 720 (ATF3+)
- Fiat 9.55550-AV5
- Bentley JNV 862 564 D

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	DRIVE 8HP
KV@ 104°F /40°C	D7042	cSt	TBR
KV @ 212°F /100°C	D7042	cSt	6.6
Viscosity Index	D2270	-	140
SP. Gravity @15°C	D4052	g/cm3	TBR
Flash Point (min)	D92	°C	200
Pour Point (max)	D97	°C	-42

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.