



ENGINE OIL TREATMENT

PRODUCT DESCRIPTION:

ENGINE OIL TREATMENT is a multi-purpose engine treatment designed to penetrate and restore surfaces susceptible to the formation of sludge and varnish. It is specially formulated to stabilize and enrich crankcase oil.

FEATURES & BENEFITS:

- Works to reduce friction & wear
- Quiets noisy lifters and valves
- Removes and prevents sludge
- Helps maintain target viscosity of engine oil
- Increases engine life due to improved oil circulation

DIRECTIONS:

Check dipstick. If oil level is low, remove oil cap and add entire contents of the bottle. Engine oil treatment may be used between oil changes, however, best results are achieved when used at each oil change. DO NOT OVERFILL.

DOSAGE:

Generally, one bottle of product will treat up to 4 to 5 quarts of oil. If engine is suspected to be heavily soiled with contaminants, a second bottle may be used. If a second bottle is used, it is recommended that the oil be changed after 100-200 miles of driving following treatment.

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	LUBREX OIL TREATMENT
Appearance	Visual		Viscous, Amber Liquid, Petroleum Odor
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	480
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm ³	0.880
Flash Point (min)	ASTM D-92	°C	>200

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.