

ENGINE CARE & FUEL ADDITIVES

Technical Data Sheet



FUEL SYSTEM CLEANER

A fast-acting blend of cleaners and detergents that you pour right into the gas tank to boost performance and gas mileage. It removes deposits in combustion chambers, intake manifolds, ports, and valves and restores flow in fuel injectors. With regular use, it keeps the entire fuel system clean and operating at peak performance, helping fuel to burn completely and cleanly, reducing emissions.

APPLICATION:

- · Recommended for use in all naturally-aspirated gas engines
- Gas turbo engines
- · Gas super-charged engines

FEATURES & BENEFITS:

- · Restores engine performance loss due to dirty fuel system
- Improves fuel combustion
- · Cleans fuel injectors
- · Cleans carburetors
- Keeps fuel system clean
- Contains NO alcohol
- · Contains PEA Technology
- · No environmentally harmful dyes

DIRECTIONS

Pour entire contents of bottle into gas tank. One bottle treats up to 20 gallons (75.71 Liters) of fuel. Do not spill on paint or fiberglass.

Dirty Injector

Clean Injector



HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.

[™]Trademark of LUBREX, registered in various countries © 2005