



OPTIMUS LX 150-EP

PRODUCT DESCRIPTION:

Optimus LX 150-EP is a multi-purpose lithium complex-based grease developed for high temperature and long-term performance in industrial and automotive applications. The grease possesses good fretting corrosion protection, good water tolerance, resistance to water wash-out, and reliable corrosion protection combined with excellent mechanical stability and good load-carrying capabilities. It contains EP, Rust, and Anti-oxidant additives.

APPLICATIONS

This product is suitable for grease-lubricated bearings at low and high speeds including electric motors, automotive bearings, and various anti-friction bearings in the mining, petrochemical, construction, and steel industries. It has good pumpability properties and can be used in centralized lubrication systems.

PRODUCT ADVANTAGES

- Good high-temperature stability
- Extreme pressure capability
- Resistance to water washout
- Excellent rust and corrosion protection
- Long service life

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE		
		1	2	3
NLGI Grade	-	1	2	3
Thickener Type	-	Lithium complex	Lithium complex	Lithium complex
Appearance	Visual	Smooth & Homogenous	Smooth & Homogenous	Smooth & Homogenous
Work penetration @25°C,	ASTM D217	310 - 340	265 - 295	220 - 250
Copper Strip Corrosion for 24hrs @100°C,	ASTM D4048	1b max.	1b max.	1b max.
Dropping Point °C,	ASTM D566	>250	>250	>250
Wheel Bearing Leakage after 6hrs @ 105°C g,	ASTM D1263	max 5	max 5	max 5
Base Oil Viscosity @ 40 °C (cSt)	ASTM 445	150	150	150
Four Ball EP, Load Wear Scar, mm	ASTM D2266	0.6	0.6	0.6
Four Ball Weld Lead Kgf, Min	ASTM D2596	250	250	250
Water Washout resistance %WT @79°C,	ASTM D1264	max 5	max 5	max 5
Oil separation %, 30hrs @100°C,	ASTM D6184	max 5	max 5	max 5

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with grease may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used grease in to drains or the environment. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.