



## SUPER SCOOTER

### PRODUCT DESCRIPTION:

Super Scooter is formulated from high-quality base stocks and mixed with several additives with a stable thermal detergent system to improve engine cleanliness and durability. This lubricating oil serves to treat and reduce friction as well as provide protection for motorcycle engines. JASO MB lubricant ensures optimal engine performance and fuel economy on all scooters without a wet clutch.

### APPLICATION:

For scooters without wet clutch and where JASO MB specification is required.

### FEATURES & BENEFITS:

- Contains Detergent Additive System with Thermal Stable to control deposit levels.
- Protects the engine from deposits optimally and the engine life increases longer.
- Has a high level of viscosity which makes the engine sound smoother.

### PERFORMANCE LEVELS: Meets or Exceeds:

- API SL
- JASO MB

### TYPICAL PROPERTIES:

| PARAMETERS                        | TEST METHOD | UNIT     | SUPER SCOOTER |        |
|-----------------------------------|-------------|----------|---------------|--------|
|                                   |             |          | 10W-30        | 10W-40 |
| Grade                             |             |          | 10W-30        | 10W-40 |
| Kinematic Viscosity @ 104°F/40°C  | ASTM D7042  | cSt      | TBR           | TBR    |
| Kinematic Viscosity @ 212°F/100°C | ASTM D7042  | cSt      | 11.90         | 14.0   |
| Viscosity Index                   | ASTM D2270  | -        | 145           | 145    |
| SP.Gravity @15°C/60 °F            | ASTM D4052  | g/cm3    | TBR           | TBR    |
| Flash Point                       | ASTM D92    | °C       | 220           | 220    |
| Pour Point                        | ASTM D97    | °C       | -36           | -36    |
| TBN                               | ASTM D2896  | Mg KOH/g | 7.0           | 7.0    |

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.