



OPTIMUS L 100-M3

PRODUCT DESCRIPTION:

Optimus L 100-M3 grease is based on lithium 12-Hydroxystearate soap and high-quality mineral base oil. The grease contains antioxidants, rust and corrosion inhibitors, extreme pressure, and anti-wear additives. The addition of molybdenum disulfide is providing extra protection against wear and shock loads. This grease contains 3% of Molybdenum disulfide.

APPLICATIONS

Optimus L 100-M3 grease is a multi-purpose grease suitable for a wide range of applications. It can be applied to lubrication points found on dozers, scrapers, earthmovers, cranes, shovels, rollers, combines, and cotton pickers. These lubrication points include most types of antifriction bearing arrangements from plain sleeve-types to rolling element bearings, as well as bushings and other sliding surface or pivot point.

PRODUCT ADVANTAGES

- The operating temperature range is from -20°C to 120°C
- The presence of moly provides additional protection against wear
- Excellent load-carrying capacity
- Good resistance against water
- Good mechanical stability
- Good corrosion protection

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE	
		2	3
NLGI Grade	-	2	3
Thickener Type	-	Lithium 12-Hydroxystearate	Lithium 12-Hydroxystearate
Appearance	Visual	Smooth & Homogenous	Smooth & Homogenous
Color	Visual	Dark gray	Dark gray
Work Penetration @25°C,	ASTM D217	265-295	220-250
Copper Strip Corrosion 24hrs @100°C	ASTM D4048	1b max.	1b max.
Dropping Point °C, Min	ASTM D2265	180	180
Water Washout Resistance %Wt. @79°C	ASTM D1264	max 10	max 10
Four Ball, Load Wear Scar, Mm	ASTM D2266	0.6	0.6
Four Ball Weld Load, Kgf, Min	ASTM D2596	200	200
Dry Lubricant	-	Molybdenum Disulfide	Molybdenum Disulfide
Operating Temperature Range, °C	INTERNAL	-20 to 120	
Base Oil Viscosity @40°C (Cst)	ASTM D445	90 -110	90-110

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with grease may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used grease in to drains or the environment. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.