



E-THERMOTRON BATTERY FLUID

PRODUCT DESCRIPTION:

E-Thermotron is a biodegradable dielectric fluid with excellent heat removal capacity and high oxidation resistance. It is especially suitable for direct cooling (immersion) through direct contact with electric vehicle components, such as batteries, electric motors, or inverters that require good temperature control to optimize their performance.

APPLICATION:

Recommended for immersion cooling of electric vehicle components.

FEATURES & BENEFITS:

- Readily biodegradable
- Excellent dielectric properties
- High oxidation resistance.
- Given its good thermal properties, it has a very wide operating temperature range and shows exceptional behavior at very low temperatures.
- Good fire-resistant properties, since its ignition point is greater than 300°C

PERFORMANCE LEVELS: Meets or Exceeds:

- Type K fluid according to IEC 61100.
- In compliance with IEC 61099 standard for organic and synthetic esters

TYPICAL PROPERTIES:

PARAMETERS	ASIM	UNIT	E-THERMOTRON
Kinematic Viscosity @ -20°C	ASTM	cSt	<1000
Flash Point	ASTM D-92	°C	>200
Pour Point	ASTM D-97	°C	-51
Specific heat at 25°C	ASTM E1269	J/kg-K	1900
Thermal conductivity at 25°C	ASTM D7896	W/m-K	0.145
Dielectric breakdown voltage	IEC 60156	kV	75
Resistance at 90°C	IEC 60247	G Ohm.m	7
Biodegradability over 28 days	OECD 301B	%	70

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with battery fluid may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained.

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend storing all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.