



MOMENTA PLATINUM NEO SYNTHETIC / SEMI SYNTHETIC / MINERAL

PRODUCT DESCRIPTION:

Momenta Platinum NEO is an advanced semi synthetic heavy-duty diesel engine oil that is specifically engineered to deliver longer oil drain intervals. It helps extend engine life in the most severe on and off-highway applications while delivering outstanding performance in modern high output low-emission engines fitted with EGR. Momenta Platinum NEO is also compatible with the latest exhaust after-treatment systems such as DPF, DOC and SCR. The exceptional low temperature fluidity and pumpability in combination with the sophisticated additive system, ensures maximum engine wear protection and supports longer engine life.

APPLICATION:

Momenta Platinum NEO is recommended for heavy-duty diesel engines including Euro V/VI modern low emission vehicles, utilizing technologies such as Diesel Particulate Filter (DPF), Selective Catalytic Reduction (SCR), Continuously Regenerating Traps (CRT), Diesel Oxidation Catalysts (DOC) and Exhaust Gas Recirculation (EGR). It is also recommended for High-performance diesel applications including turbo-charged designs featuring EGR technology and diesel applications using older, naturally aspirated conventional designs. On-highway heavy-duty trucking and off-highway including construction, mining, quarrying, and agriculture.

FEATURES & BENEFITS:

- Excellent control of oil thickening due to soot build-up.
- Outstanding TBN retention for long drain intervals.
- Outstanding resistance to oil consumption, oxidation, corrosive and abrasive wear.
- Designed to control aeration exceptionally
- Excellent shear stability
- Improved oxidation stability

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

SAE GRADES	0W-30	0W-40	5W-30	5W-40	10W-30	10W-40	15W-40
API	CK-4/SN	CK-4/SN	CK-4/SN	CK-4/SN	CK-4/SN	CK-4/SN	CK-4/SN
ACEA 2016	E9	E9	E9	E9	E9	E9	E9
Caterpillar	ECF-3	ECF-3	ECF-3	ECF-3	ECF-3	ECF-3	ECF-3
Volvo	VDS-4.5	VDS-4.5	VDS-4.5	VDS-4.5	VDS-4.5	VDS-4.5	VDS-4.5
Cummins	CES 20086	CES 20086	CES 20086	CES 20086	CES 20086	CES 20086	CES 20086
MB	-	-	228.31	228.31	228.31	228.31	228.31
MAN	M3775	M3775	M3775	M3775	M3775	M3775	M3775
Deutz	DQC III-18 LA	DQC III-18 LA	DQC III-18 LA	DQC III-18 LA	DQC III-18 LA	DQC III-18 LA	DQC III-18 LA
Renault	RLD3	RLD3	RLD3	RLD3	RLD3	RLD3	RLD3
Mack	EOS 4.5	EOS 4.5	EOS 4.5	EOS 4.5	EOS 4.5	EOS 4.5	EOS 4.5
DDC	-	-	93K222	93K222	93K222	93K222	93K222
MTU	-	-	Type 2.1	Type 2.1	Type 2.1	Type 2.1	Type 2.1
FORD	WSS-M2C171-F1	WSS-M2C171-F1	WSS-M2C171-F1	WSS-M2C171-F1	WSS-M2C171-F1	WSS-M2C171-F1	WSS-M2C171-F1


TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	MOMENTA PLATINUM NEO							
			0W-30	0W-40	5W-30	5W-40	10W-30	10W-40	15W-40	
Grade										
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	11.9	15.1	11.9	15.1	11.8	15.2	15.3	
Viscosity Index (min)	D2270	-	160	170	160	160	145	145	135	
SP. Gravity @15°C/ 60°F	D4052	g/cm ³	TBR	TBR	TBR	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	D92	°C	220	220	220	220	220	220	220	220
Pour Point (max)	D97	°C	-39	-39	-39	-39	-36	-36	-33	
TBN	D2896	mg KOH/g	8	8	8	8	8	8	8	8
CCS	D5293	m.Pa.S	<6200 (-35°C)	<6200 (-35°C)	<6600 (-30°C)	<6600 (-30°C)	<7000 (-25°C)	<7000 (-25°C)	< 7000 (-20°C)	

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.