



## DALENO DEMOULDING OIL FOR CEMENT PRODUCTS

### PRODUCT DESCRIPTION:

Daleno is an extremely light demoulding oil for cement products. It prevents adhesion by developing a physical film or barrier between the forming surface and the concrete. It has been specially developed for concrete demoulding where the oil creates a layer between the concrete and the mould. This layer is a critical part of the process as the chemistry of the product will result in soap formations at the interface.

### APPLICATION:

Daleno is used for tiles, cement slates, fence posts and thin flat sections and other prefab elements of medium to higher quality.

### FEATURES & BENEFITS:

- Superior quality of the surface
- Light colour
- Enriched with special additives
- Prevents sticking
- Extremely handy to apply

### TYPICAL PROPERTIES:

PARAMETERS	METHOD	UNIT	TYPICAL
Appearance	Visual	-	Bright and Clear
Density, 15 °C	D 4052	g/ml	TBR
Kinematic Viscosity, 40 °C	D 445	mm <sup>2</sup> /s	2.0
Flash Point, COC	D 92	°C	84
tv Test, Proc. A and B, 24 h	D 665	-	pass

The figures above are not a specification, They are typical figures obtained within production tolerance.

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.