



DIESEL FUEL CONDITIONER

Diesel engines are extremely sensitive to the deposits that form throughout the fuel system. Engines with deposits experience reduced fuel efficiency, engine clatter, diminished performance, and other drivability issues. Diesel Fuel Conditioner modifies the combustion of diesel fuel to allow the fuel to burn more completely and leave less carbon deposits. It helps disperse moisture from fuel system, restores fuel flow and fuel economy, and reduces exhaust emissions and smooth idle.

APPLICATION:

- Recommend in use of all diesel fuel systems
- Recommended for Tier 4 Diesel Engines

FEATURES & BENEFITS:

- Helps improve diesel engine performance
- Helps fuel injectors run cleaner
- Helps keep fuel tank, fuel lines and fuel system clean
- Helps disperse moisture from fuel system
- Helps improve fuel combustion
- No environmentally harmful dyes

DIRECTIONS:

Add contents of bottle to fluid every 10,000 miles or once a year, whichever comes first. Do not overfill. One bottle treats up to 15 gallons (56.78 Liters) of fuel.

Dirty Injector



Clean Injector



HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.