



## DRIVEMAX III SYNTHETIC

### PRODUCT DESCRIPTION:

Drivemax III is a fully synthetic automatic transmission fluid formulated with premium, severely hydro processed base stocks and additives that helps provide oxidation and thermal stability, friction control, load-carrying ability, corrosion and wear protection. It helps protect against the formation of deposits, sludge, varnish, foam and provide outstanding durability.

### APPLICATION:

Suitable for automatic gearboxes of passenger cars, heavy-duty automatic transmissions, power steering units and hydraulic systems requiring Dexron III G and Allison C-4 fluids.

### FEATURES & BENEFITS:

- It provides protection against the formation of lacquers, sludge or other harmful deposits
- Exceptional stability provided by excellent base oil and extra oxidation inhibitors
- Especially effective in minimizing transmission "chatter." Helps ensure smooth, quiet action at all speeds
- It ensures fast circulation during cold weather and excellent lubrication when hot

### OEM Approvals:

- ZF TE-ML 04D, 14A
- VOITH H55.6335.xx

### PERFORMANCE LEVELS: Meets or Exceeds:

- GM DEXRON III G, III H
- ZF TE-ML 14A, 03D, 04D, 17C, 09C
- VOITH 55.6336.3x
- MAN 339 TYPE V1/Z1/V2/Z2
- MB 236.1/236.10/236.5/236.6/236.9
- ALLISON TES-389
- VOLVO 1161621, 97341
- FORD M, FORD TASA
- ALLISON C4

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	DRIVEMAX III
Kinematic Viscosity @ 104°F /40°C	ASTM D7042	cSt	34.5
Kinematic Viscosity @ 212°F /100°C, min	ASTM D7042	cSt	7.2
Viscosity Index	ASTM D2270	-	180
SP. Gravity @15°C/ 60°F	ASTM D4052	g/cm <sup>3</sup>	0.850
Flash Point (min)	ASTM D92	°C	200
Pour Point (max)	ASTM D97	°C	-42

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

### HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

### STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.