



DRIVEMAX ZFL

Heavy Duty Transmission Oil for ZF Long Drain

PRODUCT DESCRIPTION:

Drivemax ZFL is a fully synthetic, premium quality, heavy duty automatic transmission oil specifically designed for the newest generation of ZF-Ecomat - and ZF- Ecolife transmissions. It is the ultimate performance automatic transmission fluid allowing longest oil drain intervals under all driving conditions.

SUITABLE FOR:  

FEATURES & BENEFITS:

- Maximum oil drain interval
- Extremely low temperature fluidity
- outstanding corrosion protection
- excellent wear resistance
- very compatible with seals
- lower maintenance cost due to long drain interval
- Smooth shifting
- excellent resistance to aging

APPLICATION:

- Drivemax ZFL can be used in all ZF-Ecomat - and ZF-Ecolife transmissions, and where retarders are used.

PERFORMANCE LEVELS: Meets and Exceeds:

- ZF TE-ML 04D, 14E, 16N, 20F, 25F
- MAN 339 TYPE Z13, MAN 339 TYPE Z4

PARAMETERS	ASTM	UNIT	DRIVEMAX ZFL
KV@ 104°F /40°C	D7042	cSt	61.35
KV @ 212°F/100°C	D7042	cSt	10.20
Viscosity Index	D2270	-	155
SP. Gravity @15°C	D4052	g/cm ³	0.844
Flash Point (min)	D92	°C	230
Pour Point (max)	D97	°C	-48

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net



LUBREX
Innovative Fluid Engineering

AUTOMATIC TRANSMISSION FLUID

Technical Data Sheet



HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.