



DUNE PRO FULLY SYNTHETIC

PRODUCT DESCRIPTION:

Dune Pro MX Race is a fully synthetic 4 stroke engine oil developed to obtain highest performance and protection of motorcycle engines under extreme driving conditions. The specially designed low traction coefficient synthetic ester base oil incorporated in this formulation reduces engine internal frictional losses and improves performance. It ensures increased power, ultimate engine and wet clutch protection for maximum power transfer and smooth shifting.

APPLICATION:

Dune Pro MX Race oil is recommended for air cooled and water cooled four-stroke motorcycle engines, especially developed for Motocross and Enduro motorbikes, Quads, and Snowmobiles with and without wet clutch. Dune Pro MX Race was formerly known as Rush 4T Ester.

FEATURES & BENEFITS:

- Excellent wear protection
- High shear stability and viscosity retention
- Excellent wet clutch compatibility
- High film strength for optimum lubrication

PERFORMANCE LEVELS: Meets and Exceeds:

- API SN
- JASO MA2

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	DUNE PRO (FULLY SYNTHETIC)			
Grade			5W-40	15W-50	10W-50	10W-60
Kinematic Viscosity @ 104°F / 40°C	D-7042	cSt	97.3	149.85	145.05	187.0
Kinematic Viscosity @ 212°F / 100°C	D-7042	cSt	15.5	20.5	20.5	25.5
Viscosity Index	D-2270	-	170	160	165	170
SP. Gravity @15°C/ 60°F	D-4052	g/cm ³	0.845	0.860	0.856	0.855
Flash Point (min)	D-92	°C	236	240	240	236
Pour Point (max)	D-97	°C	-42	-39	-39	-39
TBN	D-2896	Mg KOH/g	7	7	7	7
CCS, (°C)	D-5293	m.Pa.S	5900 (-30)	6500 (-20)	6600 (-25)	6700 (-25)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.