



FARMOL UTTO MINERAL

PRODUCT DESCRIPTION:

Farmol UTTO is an extra high-performance multipurpose tractor lubricant engineered to meet or exceed transmission and hydraulic fluid requirements. It is particularly well suited for reducing wet brake and Power Take-Off (PTO) chatter. It helps protect against wear and corrosion of tractor components and has excellent anti friction properties. Farmol UTTO optimises the performance of agricultural and commercial tractors operating in a wide range of environments and conditions.

APPLICATION:

Farmol oil is suitable for agricultural machinery in the areas of gearbox, engine, hydraulic systems and immersion brakes for heavy-duty tractors.

FEATURES & BENEFITS:

- Guarantees easy gear changing
- High pressure-absorption capability
- Stable to oxidation
- High resistance to aging
- Universal application
- Rationalizes storage
- High wear resistance
- Good coldstart behavior

PERFORMANCE LEVELS: Meets or Exceeds:

- API GL-4
- ALLISON C4
- Case M5 1204,6,7,9
- Caterpillar TO-2
- Ford / NewHolland FNHA-2-C-201.00
- Ford M2C-48B/C • Ford M2C-159A
- Ford M2C-86B/C • Ford M2C-134 A/B/C/D
- New Holland NH 410B
- John Deere J20 A/B/C, J14 B/C
- Massey Ferguson M1135, M1141, M1143, M 1145
- ZF TE-ML-03E, 05F, 06K

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	FARMOL UTTO	
Grade			10W-20	10W-30
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	9.0	11.6
Viscosity Index	D2270	-	140	140
Density@15°C/ 60°F	D4052	g/cm ³	TBR	TBR
Flash Point (min)	D92	°C	220	220
Pour Point (max)	D97	°C	-39	-39

DISCLAIMER: The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Lubrex reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, Registered in Various Countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.