



FRICTO CALCIUM GREASE

PRODUCT DESCRIPTION:

Lubrex Fricto Calcium greases consist of refined paraffinic base stock, calcium based thickener and special additive package. These greases possess good water resistance and can be used for lubrication of machine elements operating in conditions where water ingress cannot be avoided. These greases provide protection against rust, corrosion, wear and has outstanding ability to resist water washout.

APPLICATION:

Fricto Calcium Greases are recommended for all types of general applications of automotive and industrial purposes. It is also used for plain bearings, universal joints lubrication, nipples steering linkages and chassis suspension parts.

FEATURES & BENEFITS:

- Excellent water tolerance and is adaptable to normal grease dispensing systems including centralised lubrication systems
- Protection against rust and corrosion
- NLGI Specifications 2 & 3

NLGI GRADES:

- NLGI 2
- NLGI 3

TYPICAL PROPERTIES:

TEST	METHOD	NLGI 2	NLGI 3
Thickener Type	-	Calcium	Calcium
Colour	-	Light Brown	Light Brown
Worked Penetration @ 25°C, mm/10	ASTM D-217	265 - 295	220 - 250
Dropping Point, °C	ASTM D-2265	90	90
Operating Temperature Range, °C	-	-15 to +60	-15 to 60
Extreme Pressure	-	No	No

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.