



FRICTO MB-2

PRODUCT DESCRIPTION:

FRICTO MB-2 is a lithium thickened grease for multi purpose applications in commercial and passenger vehicle cars. It is based on mineral oil with a viscosity of about 180 cSt. The product has excellent oxidation stability and very good water resistance. It also offers excellent corrosion protection and good flow properties even at low temperatures.

APPLICATION:

FRICTO MB-2 conforms to Mercedes Benz specification 267 and it can be used as a single multi purpose grease in fleets, agricultural and construction equipment where MB page 267 specification has been recommended. It can also be used in some industrial applications where a non EP grease is suitable.

FEATURES & BENEFITS:

- Long service life
- Good oxidation and thermal stability
- Excellent pumpability in centralised systems at low temperatures.
- Improved shear stability for a stable viscosity during use
- excellent resistance to aging

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- MAN 283 Li-P 2, MB-Approval 267.0.
- NLGI 3

TYPICAL PROPERTIES:

TEST	METHOD	UNIT	RESULT
Grade	-	-	NLGI 2
Thickner Type	-	cSt	Lithium
BO, KV @ 40°C	D7042	cSt	180
Color	Visual	-	Brown
Dropping Point	D2265	°C	190

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.