

ENGINE CARE & FUEL ADDITIVES



Technical Data Sheet

FUEL INJECTOR CLEANER

A premium, low-odor detergent compound for professional fuel rail and injector cleaning using an injection tool. Fuel Injector Cleaner quickly and effectively blasts carbon deposits away from fuel injectors, combustion chambers, intake ports, and exhaust systems. Restores engine power lost due to dirty injectors and fouled combustion chambers.

APPLICATION:

- · Recommend in use of all gas naturally aspirated engines
- Gas turbo engines
- Gas supercharged engines

FEATURES & BENEFITS:

- · Cleans fuel injectors of deposits
- · Cleans combustion chamber
- Improves engine performance loss due to dirty injectors
- Contains NO alcohol
- Contains PEA Technology
- No environmentally harmful dyes

ADDED TO FUEL TANK:

- One tank port fuel injector cleanup
- Intake valve deposit cleanup
- Keeps injectors clean
- Keeps carburetors clean
- · Restores engine performance loss due to dirty fuel system

DIRECTIONS:

A. For high pressure cleaning: Follow instructions for equipment use. Disable fuel pump. Pour contents into high pressure tool and start service.

B. Pour entire contents of bottle into gas tank. One bottle treats up to 20 gallons (75.71 Liters). Do not spill on paint or fiberglass.

Dirty Injector

Clean Injector





HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www. lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, Registered in Various Countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.