



LUBREX MARINE 1530 & 1540

PRODUCT DESCRIPTION:

Lubrex Marine 1530 and 1540 are high performance trunk piston engine oils for medium speed marine and industrial type trunk piston engines operating on low Sulphur distillate fuel (Sulphur upto 1.0%). They are blended using solvent-refined high viscosity index paraffin mineral base oils with chemical additive which provide effective alkalinity, wear resistance, detergency and dispersancy.

APPLICATION:

Recommended for crankcase lubrication in medium-speed marine type diesel engines. They also be used to separate bearing lubrication and piston cooling of large crosshead type engine under severe service conditions at appropriate viscosity grades.

FEATURES & BENEFITS:

- Improved anti wear properties, reduces ring & liner wear
- Reduces port and under crown deposits
- Cleaner engine operation
- Increased protection against cylinder and bearing wear
- Outstanding thermal & oxidation stability extend periods between inspection & overhauling
- Controls black sludge deposits thus increasing oil filter life and reduces cleaning frequencies
- Excellent TBN retention with low oil consumption

PERFORMANCE STANDARDS: Meets and Exceeds:

- API CF

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	Marine 1530	Marine 1540
SAE Grade			30	40
Kinematic Viscosity @ 104°F/40°C	ASTM D-445	cSt	103	150
Kinematic Viscosity @ 212°F/100°C	ASTM D-445	cSt	11.0	15.0
Viscosity Index	ASTM D-2270	-	90	95
SP. Gravity @ 60°F	ASTM D-4052	g/cm ³	0.893	0.894
Flash Point (min)	ASTM D-92	°C	240	250
Pour Point (max)	ASTM D-97	°C	-12	-12
TBN	ASTM D-2896	Mg KOH/g	15	15



HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.