



## LUBREX MARINE 2T PLUS

### PRODUCT DESCRIPTION:

Lubrex Marine 2T Plus is a premium performance, two stroke, marine outboard engine oil formulated with a special ash less additive system. It is pre diluted with high flash point solvent to facilitate mixing with petrol at all temperatures. It is designed for engines requiring NMMA TC-W3 performance lubricants, operating in all service conditions.

### APPLICATION:

Lubrex Marine 2T Plus is recommended for use in two-stroke engines where TC-W3 or earlier lubricants are recommended. These applications include outboard engines, motorcycles, lawn mowers, scooters, golf carts, chain saws, and other two-stroke powered equipment. Lubrex Marine 2T Plus is well suited for engines using oil injection systems with fuel/oil mixture ratios of up to 150:1. Lubrex Marine 2T Plus has excellent low temperature mixing characteristics that make it suitable for use in cold climate conditions.

### FEATURES & BENEFITS:

- Maintains high power output
- Superior piston cleanliness and minimizes deposit formation
- Reduces maintenance cost due to enhanced lubricity
- Trouble free operation
- Maximizes spark plug life

### PERFORMANCE STANDARDS: Meets and Exceeds:

- NMMA TC-W3
- API TC

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	MARINE 2T PLUS
Grade			TC-W3
Kinematic Viscosity @ 104°F / 40°C	ASTM D-445	cSt	61
Kinematic Viscosity @ 212°F / 100°C	ASTM D-445	cSt	9.1
Viscosity Index	ASTM D-2270	-	127
SP. Gravity @ 60°F	ASTM D-4052	g/cm <sup>3</sup>	0.871
Flash Point (min)	ASTM D-92	°C	126
Pour Point (max)	ASTM D-97	°C	-36



**HEALTH & SAFETY, ENVIRONMENT:**

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.lubrex.net](http://www.lubrex.net)

**HEALTH & SAFETY:**

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet [www.lubrex.net](http://www.lubrex.net)

**PROTECT THE ENVIRONMENT**

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

**STORAGE:**

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.