



MOMENTA RX1 MINERAL

PRODUCT DESCRIPTION:

Momenta RX1 is a heavy-duty mineral diesel engine oil formulated with an optimized combination of base oil and an advanced additive system. It provides good protection against rust and corrosion, thermal and oxidation stability. It controls sludge build-up and deposits; hence it prolongs equipment life and reduces maintenance costs.

APPLICATION:

Recommended for wide range of turbo-charged or naturally aspirated diesel engines, generators, trucks, construction machinery, passenger cars or mixed car group comprising diesel and gasoline cars. It is recommended for automotive diesel engine of passenger cars and light commercial vehicles where the OEM recommends API CD/SF or earlier specification.

FEATURES & BENEFITS:

- Good protection against rust and corrosion
- Thermal and oxidation stability
- Controls sludge build up and deposits
- Long equipment life and reduced maintenance cost.

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API CD/SF
- MIL-L-2104D
- CAT TO-2

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	MOMENTA RX1					
			15W-40	20W-50	20W-60	40	50	60
Grade			TBR	TBR	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 104°F / 40°C	D7042	cSt	TBR	TBR	TBR	TBR	TBR	TBR
Kinematic Viscosity @ 212°F / 100°C	D7042	cSt	15.4	20.3	24.2	15.5	20.2	24.2
Viscosity Index (min)	D2270	-	135	120	120	95	95	95
Density@15°C/ 60°F	D4052	g/cm ³	TBR	TBR	TBR	TBR	TBR	TBR
Flash Point (min)	D92	°C	220	220	220	220	220	220
Pour Point (max)	D97	°C	-33	-24	-24	-9	-9	-9

DISCLAIMER: The test data provided above is not a specification but is indicative and may vary within permissible production tolerances. Lubrex reserves the right to modify this test data. Updated information will supersede previous versions, so please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

TM Trademark of LUBREX, Registered in Various Countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.