



MOMENTA NANO PLUS

SEMI SYNTHETIC

PRODUCT DESCRIPTION:

Momenta Nano Plus is a premium performance semi synthetic low emission heavy-duty engine oil designed for naturally aspirated and turbo-charged 4stroke diesel and petrol engines in on- and off-highway and construction machinery applications. It is formulated with a range of latest technology dispersant, detergent, oxidation inhibition, anti-wear, anti-corrosion, viscosity improver and foam suppression additives, and is recommended for extended drain intervals.

APPLICATION:

It is recommended for 4stroke naturally aspirated and turbo-charged diesel engines, meeting Euro IV, Euro V, and the newest Euro VI emission requirements where permitted by the OEM and is suitable for use in engines with global after-treatment systems such as Exhaust Gas Recirculation (EGR), Diesel Particulate Filter (DPF), and Selective Catalytic Reduction (SCR).

FEATURES & BENEFITS:

- Helps keep piston rings, piston lands and valves clean, and offers effective soot dispersancy and wear control, optimising engine service life and maintenance costs.
- Latest technology dispersant, detergent, oxidation inhibition, anti-wear, anti-corrosion, viscosity improver, and foam suppression protection.
- Formulated to reduce emission control system cleaning and maintenance, improving Diesel Particulate Filter (DPF) life
- Advanced semi-synthetic base oil and additive technology helps control oxidation, sludge and oil thickening, offering extended oil drain intervals.

OEM Approvals:

- Volvo VDS-4 (SAE 10W-40)
- Mack EO-O Premium Plus (SAE 10W-40)
- Renault Trucks RLD3 (SAE 10W-40)

API LICENSE:

- SAE 10W-30
- SAE 10W-40



PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API CJ-4/SM
- ACEA E9
- DTFR 15B1101
- Caterpillar ECF-3
- MAN M3477/3575
- VOLVO VDS-4
- Renault RLD3
- DDC 93K218
- Mack EO-O PP
- Cummins CES 20081
- DEUTZ DQC III-10 LA
- FORD WSS-M2C171-F1

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	MOMENTA NANO PLUS	
			10W30	10W40
Grade			10W30	10W40
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	11.7	15.1
Viscosity Index (min)	D2270	-	145	145
SP. Gravity @15°C/ 60°F	D4052	g/cm ³	TBR	TBR
Flash Point (min)	D92	°C	220	220
Pour Point (max)	D97	°C	-36	-36
TBN	D2896	mg KOH/g	10	10
CCS	D5293	m.Pa.S	<7000 (-25°C)	<7000 (-25°C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or in the environment. Dispose to an authorized used oil collection point. For further information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.