



MOMENTA NANO SEMI SYNTHETIC

PRODUCT DESCRIPTION:

Momenta Nano Semi Synthetic is a heavy-duty engine oil that provides excellent lubrication in today's diesel and gasoline engines operating in severe applications. It is designed using the high-performance base oils which provide excellent low temperature fluidity, high temperature viscosity retention and volatility control. Momenta Nano is engineered to provide a strong foundation for oxidation resistance, soot handling, and wear control. It provides excellent piston deposit protection and reduced sludge formation to help provide long engine life.

APPLICATION:

Momenta Nano Semi Synthetic provides demonstrated protection and performance in the latest high-power heavy-duty diesel engines from Europe, US, and Japanese manufacturers in both on-highway and off-highway applications. It is suitable for modern low emission engines meeting Euro 2, 3 and US 2002 emission requirements.

FEATURES & BENEFITS:

- Increased thermal and oxidation stability
- Reduced sludge buildUp, deposits and extended engine life
- Improved corrosion protection and advanced piston deposit control
- Advanced soot handling to control viscosity increase and sludge build up
- Enhanced low temperature pumpability

API LICENSE:

- SAE 10W-40



PERFORMANCE LEVELS / MEETS OR EXCEEDS:

- API CI-4/SL
- ACEA E7, A3/B3/B4
- DTRF 15B110 / 229.1
- MAN M3275-1
- Volvo VDS-3
- Deutz DQC III-10
- JASO DH1
- MACK EO-N
- Cummins CES 20076/20077/78
- Global DHD1
- Renault RLD2
- MTU Type 2
- Allison C4
- Caterpillar ECF 1a, ECF 2
- DDC 93K215

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	MOMENTA NANO	
			10W-30	10W-40
Grade			10W-30	10W-40
Kinematic Viscosity @ 104°F /40°C	D7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	D7042	cSt	11.7	15.1
Viscosity Index (min)	D2270	-	145	145
SP. Gravity @15°C/ 60°F	D4052	g/cm ³	TBR	TBR
Flash Point (min)	D92	°C	220	220
Pour Point (max)	D97	°C	-36	-36
TBN	D2896	mg KOH/g	11	11
CCS	D5293	m.Pa.S	<7000 (-25°C)	<7000 (-25°C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website www.lubrex.net

HEALTH & SAFETY:

This product is not likely to present any significant health or safety hazards when properly used in the recommended application and good standards of personal hygiene are maintained. Reference is made to the Safety Data Sheet (SDS) which is available on request via your local sales office or via the internet www.lubrex.net

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.

STORAGE:

We recommend to store all packages under cover. In case outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should never be stored above 60°C, exposed to hot sun or freezing conditions.

™ Trademark of LUBREX, registered in various countries © 2005

All statements, information and data presented herein are believed to be accurate and reliable, but are not to be taken as a guarantee, an express warranty or an implied warranty of merchantability or fitness for a particular purpose, or representation, express or implied, for which LUBREX and its affiliates assume legal responsibility.